

DELPHION**RESEARCH****PRODUCTS****INSIDE DELPHION**[Log Out](#) [Work Files](#) [Saved Searches](#)[My Account](#)[Search: Quick/Number](#) [Boolean](#) [Advanced](#) [Der](#)**Derwent Record**[✉ Etr](#)View: [Expand Details](#) Go to: [Delphion Integrated View](#)Tools: [Add to Work File](#) [Create new Wor](#)

Derwent Title: Obtaining gas mixts. for intermittent normobaric hypoxia - includes passage of initial compressed air through fibre membrane element and passage of resulting humidified air to mask of patient

Original Title: ☒ **RU2004261C1: METHOD AND APPARATUS FOR OBTAINING GASEOUS MIXTURE FOR INTERMITTENT NORMOBARIC HYPOXIA**

Assignee: MURASHOV M V Individual

Inventor: MURASHOV M V;


Accession/ 1994-115953 / 199626

Update:

IPC Code: A61M 16/00 ;

Derwent Classes: **A88; B06; J01; P34;**

Manual Codes: **A12-S05A**(Non-circular, hollow, tapered fibres) , **A12-V03B** (Respirators; oxygenating devices; blood handling apparatus and devices; birth control devices) , **A12-W11A**(Reverse osmosis; semi-permeable membranes) , **B05-C08**(Other common non-metals, compounds) , **B14-K01**(Respiratory active general and other) , **J01-C03**(Semi-permeable membrane separation processes) , **J01-E03E**(Gas separation using semi-permeable membrane)




Derwent Abstract: **(RU2004261C)** Obtaining a gas mixt. for intermittent normobaric hypoxia includes compression of initial air and passage of air through flowmeter and humidifier to patient. The initial air is compressed to a determined pressure and the membrane element is in the form of hollow polymer fibres with a 2:10 ratio of dia. to wall thickness. The humidified mixt. is passed through a receiver, flexible pipe and mask with a breathing valve.

USE/Advantage - Used for treatment of patients by intermittent normobaric hypoxia. Stable compsn. of hypoxia mixt.

Initial air passes into a body (1) and to a gas-sepn. unit (2) through a compressor (3) and also to a membrane element (4) of hollow polymer fibres. The oxygen content of the mixt. from the element (4) is regulated by a regulator (5) and the mixt. passes to a gas analyser (6), with some gas passing through a pipeline (7) and a flowmeter (9) to a humidifier (10) and then to a receiver (11).

The gas mixt. is then passed to the mask (13) of a patient with a breathing valve (14). The procedure of intermittent normobaric hypoxia is controlled by a programmer (15), having a connection to a patient pulse meter (16) and a monitor (17). The hypoxic gas mixt. from the element (14) is regulated to an oxygen content of 10% and nitrogen content of 90%.

Images:



Dwg.1/1

Family: **PDF Patent** **Pub. Date** **Derwent Update** **Pages** **Language** **IPC Code**
☒ **RU2004261C1** * 1993-12-15 199414 5 English A61M 16/00
 Local appl.: SU1991005005743 Filed:1991-09-25 (91SU-5005743)

Priority Number:

Application Number	Filed	Original Title
SU1991005005743	1991-09-25	

Chemical Indexing Codes: [Show chemical indexing codes](#)

Extended Polymer Index: [Show extended polymer index](#)

Specific Compound Numbers: [Show specific compounds](#)

Registry Numbers: 01[M2]:1779U
 Registry Numbers: 02[M2]:1738U

Unlinked Registry Numbers: 1738U 1779U

Related Accessions:

Accession Number	Type	Derwent Update	Derwent Title
C1994-053834	C		
N1994-090792	N		
2 items found			

Title Terms: OBTAIN GAS MIXTURE INTERMITTENT HYPOXIA PASSAGE INITIAL
 COMPRESS AIR THROUGH FIBRE MEMBRANE ELEMENT PASSAGE RESULT
 HUMIDIFY AIR MASK PATIENT

Pricing Current charges

Derwent Searches: [Boolean](#) | [Accession/Number](#) | [Advanced](#)

Data copyright Thomson Derwent 2003

THOMSON
 *

Copyright © 1997-2005 The Tho
 Subscriptions | Web Seminars | Privacy | Terms & Conditions | Site Map | Contact U

